






MATERIAL SAFETY DATA SHEET

Protective Clothing	NFPA Rating	Transportation
		 Not Regulated

Section 1: Product and Company Information

Product Name: Re-Spray Ceiling Texture
Product Code: 10080
MSDS Number: 10080
Synonyms: Re-Spray
Hopper Formula
Product Use: Ceiling Texture
Manufacturer: Hamilton Drywall Products
295 N. Pekin Road
Woodland, WA
98674
Phone Number: 800-871-4998
Fax Number: 800-871-5007
24-hour Emergency: CHEMTREC: (800) 424-9300

Section 2: Composition and Ingredient Information

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt. %</u>
Calcium Carbonate, Limestone	1317-65-3	60 - 80
Kaolin	1332-58-7	5 - 10
Mica	12001-26-2	5 - 15
Attapulgite Clay	12174-11-7	1 - 3
Titanium dioxide	13463-67-7	0.1 - 1
Crystalline Silica	14808-60-7	0.1 - 1

Note:
See Section 8 of this MSDS for exposure limit data for these ingredients.



MATERIAL SAFETY DATA SHEET

Section 3: Hazards Identification

Preparation Hazards and Classification:

This product is not a hazardous material as defined by 29 CFR 1910.1200, OSHA Hazard Communication Evaluation.

Appearance, Color and Odor:

White powder

Primary Route(s) of Exposure:

Inhalation, Eye contact, Skin contact

Potential Health Effects:

ACUTE (short term): see Section 8 for exposure controls.

Inhalation:

High concentrations of airborne dust and mist may cause irritation of the upper respiratory tract with symptoms such as coughing, sneezing and shortness of breath.

Ingestion:

Not an expected route of occupational exposure. If ingestion does occur, mild temporary stomach discomfort may result.

Skin:

May cause slight irritation.

Eyes:

May cause irritation as a foreign object in the eye. Tearing, blinking and mild temporary pain may result as the material is rinsed from the eye by tears.

CHRONIC (long term): see Section 11 for additional toxicological data.

In general, long-term exposures to high concentrations of dust may cause increased mucous flow in the nose and respiratory system airways. This condition usually disappears after exposure stops.

Prolonged and repeated breathing of dust may cause lung disease (pneumoconiosis). The extent and severity of lung injury correlates with the length of exposure and dust concentration.

Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.

Prolonged or repeated skin contact may dry the skin, causing cracking or dermatitis.

Medical Conditions Aggravated by Exposure:

Pre-existing upper respiratory and lung diseases, such as bronchitis, emphysema and asthma, can be aggravated by exposure to airborne dust.

Pre-existing skin conditions, such as rashes and dermatitis, can be aggravated by skin exposure.

Section 4: First Aid Measures

Inhalation:

If symptoms are experienced, remove source of contamination or move victim to fresh air. If symptoms persist, obtain medical advice immediately.

Eye Contact:

Do not allow victim to rub eye(s). Let the eye(s) water naturally for a few minutes. Have victim look right and left, and then up and down. If particle/dust does not dislodge, flush with lukewarm, gently flowing water for 15 minutes or until particle/dust is removed, while holding the eyelid(s) open. If irritation persists, obtain medical attention. DO NOT attempt to manually remove anything stuck to eye(s).

Skin Contact:

If irritation does occur, quickly and gently blot away excess chemical. Wash gently and thoroughly with water and non-abrasive soap for 5 minutes or until the chemical is removed. If irritation persists, obtain medical advice immediately.

Ingestion:

If irritation or discomfort occurs, obtain medical advice immediately.



MATERIAL SAFETY DATA SHEET

Section 5: Fire Fighting Measures

<u>Flash Point and Method (°C):</u>	Not applicable
<u>Flammability Limits (%):</u>	Not applicable
<u>Auto Ignition Temperature (°C):</u>	Not applicable
<u>Extinguishing Media:</u>	This material is not flammable, use extinguishing media that are appropriate for the surrounding fire conditions.
<u>Unusual Fire and Explosion Hazards:</u>	Sensitivity to mechanical impact: Not sensitive Sensitivity to static discharge: Not sensitive
<u>Fire Fighting Instructions:</u>	Evacuate area and fight fire from safe distance. Wear pressure-demand self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear. As with any fire, toxic gases, vapors and fumes can be generated.
<u>Hazardous Combustion Products:</u>	Products of incomplete combustion may include oxides of carbon and dense smoke.

Section 6: Accidental Release Measures

<u>Personal Precautions:</u>	Wear adequate personal protective equipment as indicated in Section 8. Isolate spill area, preventing entry by unauthorized persons. Ventilate area of spill if there is excessive airborne dust.
<u>Environmental Precautions:</u>	Minimize entry of material into sewers and drainage systems. Refer to permit discharge limitations if applicable.
<u>Methods for Containment:</u>	Contain spill immediately. Scrape and scoop material into a secure container for disposal. Dry sweeping of dust is not recommended. Avoid raising dust.
<u>Methods for Clean-up:</u>	Avoid dust generation. Avoid inhalation of dust and contact with eyes and skin. Wear appropriate protective equipment. Maintain proper ventilation. If vacuum is used to collect dust, use an industrial vacuum cleaner with a high efficiency air filter. Do not dry-sweep. If sweeping is necessary, use dust suppressant. Do not use compressed air for clean up. Do not wash the paste down the drain as it may cause the drain to plug.

Section 7: Handling and Storage

<u>Handling:</u>	Keep containers closed when not in use. Avoid generating dusts. Good housekeeping is important to prevent accumulations of dust. Prevent the release of dusts into the workplace air. Do not allow dust to collect on walls, floors, ledges or equipment.
<u>Storage:</u>	Store in suitable, labeled containers. Protect from damage. Do not freeze. Keep product out of direct sunlight at all times. Keep storage containers closed when not in use.



MATERIAL SAFETY DATA SHEET

Section 8: Exposure Controls and Personal Protection

<u>Ingredient</u>	<u>ACGIH TLV</u> <u>(8-hr. TWA)</u>	<u>U.S. OSHA PEL</u> <u>(8-hr. TWA)</u>
Calcium Carbonate, Limestone	10	15 (total dust) 5 (respirable fraction)
Kaolin	2	15 (total dust) 5 (respirable fraction)
Mica	3 (respirable)	20 mppcf* (less than 1% crystalline silica)
Attapulgate Clay	Not established	Not established
Titanium dioxide	10	15 (total dust)
Crystalline Silica	0.025 (respirable)	quartz (total dust): 30 mg/m ³ / (%SiO ₂ + 2) quartz (respirable): 10 mg/m ³ / (%SiO ₂ + 2)

Engineering Controls:

Local exhaust ventilation is the preferred method to minimize dust and mist. General mechanical exhaust can also be used if needed.

Hygiene Measures:

Wash hands thoroughly after handling this material. Maintain good housekeeping.

Personal Protective Equipment

Respiratory Protection:

Wear a dust mask when dry sanding and when handling dry product. Wear a NIOSH/MSHA-approved respirator equipped with particulate cartridges when dusty in poorly ventilated areas, and if exposure limits are exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection:

Wear gloves and protective clothing to prevent repeated or prolonged skin contact.

Eye Protection:

Wear safety glasses or splash goggles to avoid eye irritation.



MATERIAL SAFETY DATA SHEET

Section 9: Physical and Chemical Properties

Physical State:	Solid	Vapor Pressure: (mm Hg @ 25°C)	Not available
Appearance:	White powder	Vapor Density: (Air = 1)	Not available
pH:	7 to 10 (aqueous slurry)	Solubility in Water:	Not available
Relative Density (water = 1):	Not available	Water / Oil distribution coefficient:	Not available
Boiling Point:	Not applicable	Odor Type:	Odorless
Freezing Point:	Not applicable	Odor Threshold:	Not available
Viscosity:	Not available	Evaporation Rate: (n-Butyl Acetate = 1)	Not available
Oxidizing Properties:	Not available	Auto Ignition Temperature (°C):	Not applicable
Flash Point and Method:	Not applicable	Flammability Limits (%):	Not available

Section 10: Stability and Reactivity

Stability:	Stable
Incompatible Materials and Conditions to Avoid:	Incompatible with acids and strong oxidizing agents.
Hazardous Decomposition Products:	Products of incomplete combustion may include oxides of carbon and dense smoke.
Hazardous Polymerization:	Will not occur.

Section 11: Toxicological Information

Acute Toxicity Data:

Ingredient	LD₅₀ Oral (mg/kg)	LD₅₀ Dermal (mg/kg)	LC₅₀ Inhalation (mg/m³, 4 hrs.)
Calcium Carbonate, Limestone	6 450 (rat)	Not established	Not established
Kaolin	Not available	Not available	Not available
Mica	Not available	Not available	Not available
Attapulgate Clay	Not available	Not available	Not available
Titanium dioxide	>10 000 (mouse)	>6 820 (rat)	Not available
Crystalline Silica	Not available	Not available	Not available



MATERIAL SAFETY DATA SHEET

Section 11: Toxicological Information, continued

Chronic Toxicity Data

Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen.

<u>Ingredient</u>	<u>ACGIH</u>	<u>IARC</u>	<u>NTP</u>
Calcium Carbonate, Limestone	Not listed	Not listed	Not listed
Kaolin	Not listed	Not listed	Not listed
Mica	Not listed	Not listed	Not listed
Attapulgitte Clay	A4	Group 2B (fibre <5um) Group 3 (fibre >5um)	Not listed
Titanium dioxide	A4	Group 2B	Not listed
Crystalline Silica	A2	Group 1	Known human carcinogen

Carcinogenicity Designations:

ACGIH: American Conference of Governmental Industrial Hygienists

A2 – Suspected Human Carcinogen.

A4 - Not classifiable as a human carcinogen.

IARC: International Agency for Research on Cancer

Group 1 – Carcinogenic to humans.

Group 2B - Possibly carcinogenic to humans.

Group 3 – Not classifiable as to its carcinogenicity in humans

NTP: National Toxicity Program

Irritation: Exposure to airborne dust may cause irritation of the upper respiratory tract and eyes. Skin contact may cause slight irritation.

Sensitization: Not applicable

Neurological Effects: Not applicable

Teratogenicity: Not applicable

Reproductive Toxicity: Not applicable

Mutagenicity: Not applicable

Toxicologically Synergistic Materials: Not applicable

Section 12: Ecological Information

Movement and Partitioning: Not available

Degradation and Persistence: Not available

Ecotoxicity: Not available

Other: Not available



MATERIAL SAFETY DATA SHEET

Section 13: Disposal Considerations

Waste Disposal Method: Do not discharge into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.

USA: Dispose of in accordance with local, state and federal laws and regulations.
RCRA: None listed

Section 14: Transport Information:

U.S. Hazardous Materials Regulation (DOT 49CFR): Not Regulated

ADR/RID: Not Regulated

IMDG: Not Regulated

ICAO/IATA : Not Regulated

Section 15: Regulatory Information

NFPA Hazard Rating:



TSCA Status: All ingredients are listed in the TSCA inventory.

SARA Title III:

Sec. 302/304: None
Sec: 311/312: Crystalline Silica: chronic
Sec. 313: None
CERCLA : None

Right to Know: Crystalline Silica: NJ, PN, MN, MA
Calcium carbonate: PN, (listed as Calcium carbonate), MN, (listed as Calcium carbonate), MA, (listed as Calcium carbonate).
Kaolin: CA (listed as Silica, amorphous), NJ (listed as Silica, amorphous), PN, MN MA
Calcium carbonate: PN, (listed as Calcium carbonate), MN, (listed as Calcium carbonate), MA, (listed as Calcium carbonate).
Titanium Dioxide: NJ, PN, MN, MA

California Proposition 65: Chemicals known to the State of California to cause cancer: Attapulgitte Clay > 5µm in length; Crystalline silica (airborne particulates of respirable size)



MATERIAL SAFETY DATA SHEET

Section 16: Other Information

Preparation Information

Prepared by: LEHDER Environmental Services Limited
704 Mara Street, Suite 210
Pt. Edward, ON
N7V 1X4
www.lehder.com

Phone: (519) 336-4101

Preparation date: March 6, 2007

Disclaimer: While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.

**Manufacturer
Disclaimer:** This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Hamilton Drywall Products. The data on this sheet relates only to the specific material designated herein. Hamilton Drywall Products assumes no legal responsibility for the use or reliance upon this data.