

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US - OSHA Hazard Communication Standard (29 CFR 1910.1200)

Issuing Date 26-May-2023 Revision Date 13-Jun-2023 Revision Number 3

1. Identification

Product identifier

Product Name EZ Spray Wall Texture (Aerosol)

Other means of identification

Product Code(s) 858193006183 (Part #13500)

850022163227 (Part #55255) 850022163241 (Part #55260)

UN/ID no UN1950

Synonyms EZ Spray Orange Peel Wall Texture - Product Code: 850022163227 (Part #55255)

EZ Spray Knockdown Wall Texture - Product Code: 850022163241 (Part #55260)

Recommended use of the chemical and restrictions on use

Recommended use Patching orange peel and knock-down texture wall and ceiling patterns

Restrictions on useUse only for intended applications

Details of the supplier of the safety data sheet

Supplier Address

Westpac Materials 341 West Meats Avenue Orange, CA, USA

92865

E-mail info@westpacmaterials.com

Website www.hamiltonnw.com

Emergency telephone number

Company Phone Number 1-866-974-6837

Emergency telephone Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

Revision Date: 13-Jun-2023

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Flammable aerosols	Category 1
Gases under pressure	Compressed gas
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1

Hazards not otherwise classified (HNOC)

Not applicable.

Label elements

Danger



Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause cancer.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/clothing and eye/face protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other information

No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Trade secret
Calcium carbonate	1317-65-3	43 - 49	*
Dimethyl ether	115-10-6	10 - 13	*
Kaolin	1332-58-7	1 - 4	*
Mica	12001-26-2	1 - 3	*
Attapulgite	12174-11-7	0.2 - 1	*
Barium metaborate	13701-59-2	0.2 - 1	*
Quartz	14808-60-7	0 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Ingestion Rinse mouth.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination.

Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer. May cause adverse reproductive effects - such as birth defect,

miscarriages, or infertility. Causes damage to organs through prolonged or repeated

exposure.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

(M)SDS Number UL-WPM-001

Revision Date: 13-Jun-2023

Specific hazards arising from the chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.

Revision Date: 13-Jun-2023

Explosion data

Personal precautions

Sensitivity to mechanical impact Yes. Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

role and procedure, procedure equipment and emergency procedures

Evacuate personnel to safe areas. Deny entry to unauthorized and unprotected personnel. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Other information \

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop lea

Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture: Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight.

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium carbonate 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³	TWA: 10 mg/m ³ total dust respirable dust
Kaolin 1332-58-7	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	respirable fraction TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Mica 12001-26-2	TWA: 0.1 mg/m³ respirable particulate matter	TWA: 20 mppcf respirable dust <1% Crystalline silica (vacated) TWA: 3 mg/m³ respirable dust <1% Crystalline silica TWA: 20 mppcf <1% Crystalline silica	IDLH: 1500 mg/m³ TWA: 3 mg/m³ containing <1% Quartz respirable dust
Attapulgite 12174-11-7	TWA: 1 mg/m ³ respirable particulate matter	-	-
Quartz 14808-60-7	TWA: 0.025 mg/m³ respirable particulate matter	TWA: 50 µg/m³ (vacated) TWA: 0.1 mg/m³ respirable dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust
Barium metaborate 13701-59-2	STEL: 6 mg/m³ inhalable particulate matter TWA: 0.5 mg/m³ Ba TWA: 2 mg/m³ inhalable particulate matter	TWA: 0.5 mg/m³ Ba regulated under CAS 7440-39-3 (vacated) TWA: 0.5 mg/m³ Ba	IDLH: 50 mg/m³ Ba TWA: 0.5 mg/m³ except Barium sulfate Ba

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Revision Date: 13-Jun-2023

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state Aerosol
Color Off-white
Odor Sweet Ether-like
Odor threshold No data available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH 8 - 10

pH (as aqueous solution)No data availableMelting point / freezing pointNo data availableInitial boiling point and boiling rangeNo data availableFlash pointNo data availableEvaporation rateNo data available

Flammability Extremely flammable aerosol

Flammability Limit in Air

Upper flammability or explosive limitsNo data availableLower flammability or explosive limitsNo data availableVapor pressureNo data availableRelative vapor densityNo data available

Relative density 1.0 - 1.4 Water = 1

Water solubility
Solubility(ies)
No data available
Partition coefficient
No data available
Autoignition temperature
No data available
Decomposition temperature
No data available

Dynamic viscosity 700 - 900 cP

Other information

Explosive properties

Oxidizing properties

No information available

VOC content 11.6% with water; 16.6% without water (calculated)

VOC <150 g/L Material VOC

<225 g/L VOC without water (calculated)

MIR < 0.2

Revision Date: 13-Jun-2023

Liquid DensityNo information availableBulk densityNo information available

10. Stability and reactivity

Reactivity None under normal use conditions.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Heat, flames and

sparks. Extremes of temperature and direct sunlight. Temperatures above 50 °C / 122 °F.

Incompatible materials Strong oxidizing agents, strong acids, and strong bases.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document:

ATEmix (inhalation-gas) 617,050.00 ppm

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Dimethyl ether	-	-	= 164000 ppm (Rat)4 h
115-10-6			
Kaolin 1332-58-7	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rat)	-
Barium metaborate 13701-59-2	= 530 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 3.5 mg/L (Rat)4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity May cause cancer. Contains a known or suspected carcinogen. Classification based on

data available for ingredients.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Attapulgite 12174-11-7	-	Group 2B Group 3	-	X
Quartz 14808-60-7	A2	Group 1	Known	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity May damage fertility or the unborn child. Classification based on data available for

ingredients.

STOT - single exposure No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Target organ effects Respiratory system. Eyes. Skin. Lungs. Gastrointestinal tract (GI).

Aspiration hazard No information available.

Other adverse effects No information available.

Interactive effectsNo information available.

12. Ecological information

EcotoxicityThe environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	-

Revision Date: 13-Jun-2023

Revision Date: 13-Jun-2023

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Dimethyl ether 115-10-6	-0.18
Barium metaborate 13701-59-2	0.69897

Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

DOT

UN/ID no UN1950 **AEROSOLS** Proper shipping name

Transport hazard class(es) 2.1 **Special Provisions** N82 **DOT Marine Pollutant** NΡ

Description UN1950, AEROSOLS, 2.1

Emergency Response Guide

Number

IATA

UN number or ID number UN1950

Aerosols, flammable **UN** proper shipping name

Transport hazard class(es)

Description UN1950, Aerosols, flammable, 2.1

Special Provisions A145, A167, A802

ERG Code 10L

IMDG

UN number or ID number UN1950 UN proper shipping name **AEROSOLS**

Transport hazard class(es) 2.1 Marine pollutant

Description UN1950, AEROSOLS, 2.1 **Special Provisions** 63,190, 277, 327, 344, 381, 959

EmS-No. F-D, S-U

15. Regulatory information

International Inventories

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Barium metaborate - 13701-59-2	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65
Attapulgite - 12174-11-7	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Calcium carbonate 1317-65-3	X	X	X
Dimethyl ether 115-10-6	X	X	X
Kaolin 1332-58-7	X	X	X
Mica 12001-26-2	X	X	X
Quartz 14808-60-7	X	X	X
Barium metaborate	X	-	X

13701-59-2

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA
HMISHealth hazards0Flammability4Instability0Special hazards-Chronic Hazard Star Legend* = Chronic Health Hazard* = Chronic Health Hazard* = Chronic Health Hazard* = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Issuing Date 26-May-2023

Revision Date 13-Jun-2023

Revision Note SDS sections updated: 3

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Revision Date: 13-Jun-2023